Bohnenkamp
Moving Professionals

WINDPOWER
Get Your Job Done



Pneu 8.25 R 15, WSR 36
18 PR, 143 / 141 G (141 / 140 J), TT, M+S
cam.+flap, TR 444, VA, Windpower

Product-No.: 10466391

Hints and features:

- Cea mai nouă generatie de anvelope pentru puntea directoare pentru transportul local si regional.
- Manevrabilitate optimizată pe carosabile uscate si umede.
- Îmbunătătirea capacitătii de respingere a apei.

Technical Information:

Product number	10466391
Tyre Size	8.25 R 15
R / D	Radial
TL / TT	TT
LI / SI	143 / 141 G (141 / 140 J)
PR	18
Profil	WSR 36
Manufacturer	Windpower
Specification	M+S, Tub + bandă talon
Recom. Rim	6.50
Permissible rim	6.00, 7.00
Width mm	238
Outer diameter mm	832
Static radius mm	386
Rolling circumference mm	2538
Payload in kg at kph (1)	2725 / 90
Payload in kg at kph (2)	2575 / 100
Inflation pressure bar	8,50
Weight kg	36,7
Rolling resistance	D
Wet grip	C
Rolling noise DB	71
Rolling noise level	B
Stud height mm	13,0
Certified	ECE 54, ECE 117
M+S	M+S
Nominal width [inch]	8.25
LI 4	140

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.