

WINDPOWER
Get Your Job Done



Pneu 315 / 80 R 22.5, WDR 37
18 PR, 154 / 151 M (156 / 150 L), TL, 3PMSF
HA, Windpower

Product-No.: 10466615

Technical Information:

Product number	10466615
Tyre Size	315 / 80 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	154 / 151 M (156 / 150 L)
PR	18
Profil	WDR 37
Manufacturer	Windpower
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.75
Width mm	320
Outer diameter mm	1096
Static radius mm	508
Rolling circumference mm	3343
Payload in kg at kph (1)	3750 / 130
Payload in kg at kph (2)	4000 / 120
Inflation pressure bar	8,30
Weight kg	74,8
Rolling resistance	E
Wet grip	C
Rolling noise DB	74
Rolling noise level	B
Stud height mm	23,0
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	315
Aspect ratio	80
LI 4	150
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.