



Pneu 295 / 60 R 22.5, WDR 55
18 PR, 149 / 146 L (150 / 147 K), TL, 3PMSF
HA, Windpower

Product-No.: 10466629

Technical Information:

Product number	10466629
Tyre Size	295 / 60 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	149 / 146 L (150 / 147 K)
PR	18
Profil	WDR 55
Manufacturer	Windpower
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.75
Width mm	288
Outer diameter mm	925
Static radius mm	430
Rolling circumference mm	2821
Payload in kg at kph (1)	3250 / 120
Payload in kg at kph (2)	3350 / 110
Inflation pressure bar	9,00
Weight kg	48,07
Rolling resistance	E
Wet grip	C
Rolling noise DB	75
Rolling noise level	B
Stud height mm	22,5
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	295
Aspect ratio	60
LI 4	147
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.