

WINDPOWER
Get Your Job Done



Pneu 315 / 80 R 22.5, WSR 36
18 PR, 158 / 150 L (154 / 150 M), TL, 3PMSF
VA, Windpower

Product-No.: 10466761

Technical Information:

Product number	10466761
Tyre Size	315 / 80 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	158 / 150 L (154 / 150 M)
PR	18
Profil	WSR 36
Manufacturer	Windpower
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.75
Width mm	315
Outer diameter mm	1082
Static radius mm	501
Rolling circumference mm	3300
Payload in kg at kph (1)	4250 / 120
Payload in kg at kph (2)	3750 / 130
Inflation pressure bar	9,00
Weight kg	68,4
Rolling resistance	C
Wet grip	C
Rolling noise DB	71
Rolling noise level	A
Stud height mm	16,5
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	315
Aspect ratio	80
LI 4	150
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.