



Pneu 275 / 70 R 22.5, MAR26  
18 PR, 148 / 145 M, TL, 3PMSF  
VA/HA/TR, Dynamo

Product-No.: 11666250

Technical Information:

|                          |                 |
|--------------------------|-----------------|
| Product number           | 11666250        |
| Tyre Size                | 275 / 70 R 22.5 |
| R / D                    | Radial          |
| TL / TT                  | TL              |
| LI / SI                  | 148 / 145 M     |
| PR                       | 18              |
| Tread                    | MAR26           |
| Manufacturer             | Dynamo          |
| Specification            | 3PMSF           |
| Recom. Rim               | 8.25            |
| Permissible rim          | 9.00            |
| Width mm                 | 275             |
| Outer diameter mm        | 958             |
| Rolling circumference mm | 2922            |
| Payload in kg at kph (1) | 3150 / 130      |
| Inflation pressure bar   | 9,00            |
| Weight kg                | 47,1            |
| Rolling resistance       | D               |
| Wet grip                 | C               |
| Rolling noise DB         | 72              |
| Rolling noise level      | B               |
| Stud height mm           | 14,5            |
| Certified                | ECE 54, ECE 117 |
| M+S                      | M+S             |
| 3PMSF                    | 3PMSF           |
| Nominal width [mm]       | 275             |
| Aspect ratio             | 70              |
| Tread symmetry           | simetrice       |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.