Bohnenkamp
Moving Professionals



Pneu 315 / 80 R 22.5, MDM60 18 PR, 156 / 150 K, TL, 3PMSF HA, Dynamo

Product-No.: 11666355

Technical Information:

Product number	11666355
Tyre Size	315 / 80 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	156 / 150 K
PR	18
Profil	MDM60
Manufacturer	Dynamo
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.75
Width mm	312
Outer diameter mm	1076
Rolling circumference mm	3282
Payload in kg at kph (1)	4000 / 110
Inflation pressure bar	8,50
Weight kg	74,8
Rolling resistance	E
Wet grip	C
Rolling noise DB	76
Rolling noise level	B
Stud height mm	22,0
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	315
Aspect ratio	80
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.