Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu 600 / 50 R 22.5, Floatmax FT 159 D, TL, Steel Belted CEAT

Product-No.: 15116240

Technical Information:

Product number	15116240
Tyre Size	600 / 50 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	159 D
Profil	Floatmax FT
Manufacturer	CEAT
Specification	Steel Belted
Recom. Rim	AG20.00
Width mm	611
Outer diameter mm	1172
Static radius mm	572
Rolling circumference mm	3459
Payload in kg at kph (1)	4375 / 65
Payload in kg at kph (2)	5950 / 40
Inflation pressure bar	4,00
Weight kg	115,08
Tyre content 75% litre	265.00
Number of studs	20x2
Certified	ECE 106
Nominal width [mm]	600
Aspect ratio	50
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Floatmax FT este o anvelopă radială pentru remorci agricole.
- Profilul directional al benzii de rulare, cu crampoane robuste, asigură o tractiune foarte bună, aderentă si auto-curătare.
- Blocurile robuste din centrul benzii de rulare si lătimea mare a benzii de rulare permit un comportament bun la rulare în timpul deplasării pe drumuri si o compactare mai redusă a solului în timpul lucrărilor pe câmp.
- Umărul rotunjit al anvelopei previne deteriorarea solului si a plantelor.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.