Bohnenkamp
Moving Professionals

CEAT SPECIALTY

Pneu IF 600 / 70 R 30, Torquemax
165 D, TL
CEAT

Product-No.: 15126845

Technical Information:

Product number	15126845
Tyre Size	IF 600 / 70 R 30
R / D	Radial
TL / TT	TL
LI / SI	165 D
Profil	Torquemax
Manufacturer	CEAT
Specification	R1-W
Recom. Rim	DW21L
Permissible rim	DW20L
Width mm	603
Outer diameter mm	1602
Static radius mm	726
Rolling circumference mm	4781
Payload in kg at kph (1)	5150 / 65
Payload in kg at kph (2)	5150 / 40
Inflation pressure bar	2,40
Weight kg	195,11
Tyre content 75% litre	424.00
Stud height mm	53,5
Number of studs	20x2
Certified	ECE 106
Nominal width [mm]	600
Aspect ratio	70
Tyre technology	IF
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.