Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu IF 600 / 70 R 34, Torquemax
160 D, TL
CEAT

Product-No.: 15126855

Hints and features:

- Anvelopa Ceat Torquemax este o anvelopă pentru tractoare de înaltă performantă.
- Designul său asigură o compactare mai redusă a solului, o tractiune ridicată si o bună manevrabilitate atât pe câmp, cât si la transportul pe sosea.
- Crampoanele anvelopei sunt usor înclinate în centrul benzii de rulare pentru a asigura caracteristici bune de rulare pe sosea.
- Unghiul mai plat al crampoanelor de pe umărul anvelopei asigură o tractiune excelentă în timpul lucrărilor pe câmp.
- Umerii rotunjiti ai anvelopei protejează solul si plantele.

Technical Information:

Product number	15126855
Tyre Size	IF 600 / 70 R 34
R / D	Radial
TL / TT	TL
LI / SI	160 D
Profil	Torquemax
Manufacturer	CEAT
Specification	R1-W
Recom. Rim	DW21L
Permissible rim	DW20L
Width mm	603
Outer diameter mm	1704
Static radius mm	768
Rolling circumference mm	5087
Payload in kg at kph (1)	4500 / 65
Payload in kg at kph (2)	4500 / 40
Inflation pressure bar	1,60
Weight kg	198,73
Tyre content 75% litre	463.00
Stud height mm	53,5
Number of studs	21x2
Certified	ECE 106
Nominal width [mm]	600
Aspect ratio	70
Tyre technology	IF
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.