Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu IF 520 / 85 R 38, Torquemax 167 D, TL CEAT

Product-No.: 15126900

Hints and features:

- Anvelopa Ceat Torquemax este o anvelopă pentru tractoare de înaltă performantă.
- Designul său asigură o compactare mai redusă a solului, o tractiune ridicată si o bună manevrabilitate atât pe câmp, cât si la transportul pe sosea.
- Crampoanele anvelopei sunt usor înclinate în centrul benzii de rulare pentru a asigura caracteristici bune de rulare pe sosea.
- Unghiul mai plat al crampoanelor de pe umărul anvelopei asigură o tractiune excelentă în timpul lucrărilor pe câmp.
- Umerii rotunjiti ai anvelopei protejează solul si plantele.

Technical Information:

Product number	15126900
Tyre Size	IF 520 / 85 R 38
R / D	Radial
TL / TT	TL
LI / SI	167 D
Profil	Torquemax
Manufacturer	CEAT
Specification	R1-W
Recom. Rim	DW18L
Permissible rim	DW16
Width mm	536
Outer diameter mm	1849
Static radius mm	832
Rolling circumference mm	5402
Payload in kg at kph (1)	5450 / 65
Payload in kg at kph (2)	5450 / 40
Inflation pressure bar	2,40
Weight kg	218,52
Tyre content 75% litre	498.00
Stud height mm	53,5
Number of studs	20x2
Certified	ECE 106
Nominal width [mm]	520
Aspect ratio	85
Tyre technology	IF
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.