Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu 560 / 60 R 22.5, Floatmax RT 165 D, TL, Steel Belted CEAT

Product-No.: 15116228

Technical Information:

Product number	15116228
Tyre Size	560 / 60 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	165 D
Profil	Floatmax RT
Manufacturer	CEAT
Specification	Steel Belted
Recom. Rim	AG16.00
Width mm	543
Outer diameter mm	1244
Static radius mm	561
Rolling circumference mm	3810
Payload in kg at kph (1)	5150 / 65
Payload in kg at kph (2)	6800 / 40
Inflation pressure bar	5,00
Weight kg	117
Tyre content 75% litre	264.00
Stud height mm	21,5
Certified	ECE 106
Nominal width [mm]	560
Aspect ratio	60
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Floatmax RT este o anvelopă radială pentru remorci agricole, mini-cisterne, masini de împrăstiat îngrăsăminte (masini de fertilizat) si vehicule similare.
- Profilul special permite o auto-curătare foarte bună.
- Compusul de cauciuc rezistent si carcasa din nailon puternic asigură o bună protectie împotriva uzurii premature si o capacitate mare de încărcare la viteze mari.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.