Bohnenkamp Moving Professionals



REIFEN 800 / 35 - 22.5 16 PR, 165 A8 / 162 D, TL, FLOT. 328, *DOT2016*

Product-No.: 15212673

Technical Information:

	15010070
Product number	15212673
Tyre Size	800 / 35 - 22.5
R/D	Diagonală
TL/TT	TL
LI / SI	165 A8 / 162 D
PR	16
Tread	Flotation 328
Manufacturer	Alliance
Specification	High Speed
Recom. Rim	28.00
Permissible rim	24.00
Width mm	790
Outer diameter mm	1170
Static radius mm	538
Rolling circumference mm	3640
Payload in kg at kph (1)	5150 / 40
Payload in kg at kph (2)	4750 / 65
Inflation pressure bar	3,60
Weight kg	126,71
Tyre content 75% litre	324.75
Stud height mm	26,0
Certified	nu este necesar
Nominal width [mm]	800
Aspect ratio	35
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.