Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 710 / 45 - 26.5, Forestar 644 III 20 PR, 175 A2 / 168 A8, TT, LS-2, Steel Belted Alliance

Product-No.: 15212758

Technical Information:

Product number	15212758
Tyre Size	710 / 45 - 26.5
R / D	Diagonală
TL / TT	TT
LI / SI	175 A2 / 168 A8
PR	20
Profil	Forestar 644 III
Manufacturer	Alliance
Specification	LS-2, Steel Belted
Recom. Rim	AG24.00
Width mm	695
Outer diameter mm	1345
Static radius mm	626
Rolling circumference mm	4102
Payload in kg at kph (1)	6900 / 10
Payload in kg at kph (2)	5600 / 40
Inflation pressure bar	5,50
Weight kg	223,15
Tyre content 75% litre	303.75
Stud height mm	51,0
Number of studs	16x2
Certified	ECE 106
Nominal width [mm]	710
Aspect ratio	45
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.