Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 560 / 60 R 22.5, 882
165 D, TL, Steel Belted
Alliance

Product-No.: 15215531

Technical Information:

Product number	15215531
Tyre Size	560 / 60 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	165 D
Profil	882
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	16.00
Width mm	565
Outer diameter mm	1244
Static radius mm	554
Rolling circumference mm	3736
Payload in kg at kph (1)	5150 / 65
Inflation pressure bar	4,20
Weight kg	111,6
Stud height mm	17,0
Certified	ECE 106
Nominal width [mm]	560
Aspect ratio	60
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopă "flotation" nou dezvoltată ranforsată cu centură din otel.
- Utilizat în principal pe autocisternele de transport greu si de gunoi de grajd, precum si pe masinile de împrăstiat îngrăsăminte cu utilizare mixtă pe sosea si pe câmp.
- Profil al canelurilor directionale pentru rezistentă redusă la rulare si proprietăti foarte bune de auto-curătare.
- Volum mare de aer pentru o compactare redusă a solului si capacitate portantă ridicată chiar si la o presiune atmosferică scăzută.
- Centura de otel oferă protectie suplimentară împotriva deteriorărilor prin întepare.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.