Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



# Pneu 600 / 50 R 22.5, 882
# 162 D / 159 E, TL, Steel Belted
# Alliance

**Product-No.: 15215562**

**Technical Information:**

| | |
|---|---|
| Product number | 15215562 |
| Tyre Size | 600 / 50 R 22.5 |
| R / D | Radial |
| TL / TT | TL |
| LI / SI | 162 D / 159 E |
| Profil | 882 |
| Manufacturer | Alliance |
| Specification | Steel Belted |
| Recom. Rim | 20.00 |
| Width mm | 611 |
| Outer diameter mm | 1172 |
| Static radius mm | 528 |
| Rolling circumference mm | 3565 |
| Payload in kg at kph (1) | 4750 / 65 |
| Payload in kg at kph (2) | 4375 |
| Inflation pressure bar | 4,00 |
| Weight kg | 109 |
| Stud height mm | 20,0 |
| Number of studs | 14x2 |
| Certified | ECE 106 |
| Nominal width [mm] | 600 |
| Aspect ratio | 50 |
| Direction bound | Yes |
| Tread symmetry | simetrice |

**Hints and features:**

- Anvelopă "flotation" nou dezvoltată ranforsată cu centură din otel.
- Utilizat în principal pe autocisternele de transport greu si de gunoi de grajd, precum si pe masinile de împrăstiat îngrăsăminte cu utilizare mixtă pe sosea si pe câmp.
- Profil al canelurilor directionale pentru rezistentă redusă la rulare si proprietăti foarte bune de auto-curătare.
- Volum mare de aer pentru o compactare redusă a solului si capacitate portantă ridicată chiar si la o presiune atmosferică scăzută.
- Centura de otel oferă protectie suplimentară împotriva deteriorărilor prin întepare.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.