Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 560 / 60 R 22.5, 380
164 D / 161 E, TL, Steel Belted
Alliance

Product-No.: 15215600

Technical Information:

Product number	15215600
Tyre Size	560 / 60 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	164 D / 161 E
Profil	380
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	16.00
Width mm	554
Outer diameter mm	1244
Static radius mm	555
Rolling circumference mm	3773
Payload in kg at kph (1)	5000 / 65
Payload in kg at kph (2)	4625 / 70
Inflation pressure bar	4,00
Weight kg	122,43
Tyre content 75% litre	272.43
Stud height mm	22,5
Certified	ECE 106
Nominal width [mm]	560
Aspect ratio	60
Tread symmetry	simetrice

Hints and features:

- Anvelope radiale flotation cu centură de otel ranforsată pentru lucrări de transport off-road.
- Auto-curătare foarte bună datorită spatiilor largi din profil.
- Volumul mare de aer permite capacităti de încărcare ridicate chiar si la presiuni de aer scăzute pentru protectia solului.
- Profilul său special non-directional al benzii de rulare permite o auto-curătare foarte bună si o tractiune uniformă pe teren.
- Anvelopa este potrivită numai pentru deplasări scurte pe stradă.
- Ideal pentru masinile de împrăştiat îngrăşăminte (maşini de fertilizat), cisternele de gunoi de grajd si vehiculele utilizate pe santierele de constructii.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.