Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 650 / 55 R 26.5, 885 170 D, TL, Steel Belted Alliance

Product-No.: 15216250

Technical Information:

Product number	15216250
Tyre Size	650 / 55 R 26.5
R / D	Radial
TL / TT	TL
LI / SI	170 D
Profil	885
Manufacturer	Alliance
Specification	Anvelope cu oţel armat
Recom. Rim	AG20.00
Width mm	648
Outer diameter mm	1380
Static radius mm	605
Rolling circumference mm	4208
Payload in kg at kph (1)	6000 / 65
Inflation pressure bar	4,00
Weight kg	144,96
Tyre content 75% litre	381.37
Stud height mm	26,8
Certified	ECE 106
Nominal width [mm]	650
Aspect ratio	55
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Alliance 885 a fost dezvoltată pentru utilizarea pe prese de balotat, remorci de cereale, cultivatoare, remorci agricole mai mici si vehicule remorcate similare.
- Umărul rotunjit al anvelopei si suprafata de contact mare asigură o conservare excelentă a plantelor si solului.
- Crampoanele mari centrale asigură un comportament la volan lin în timpul transportului.
- Rezistenta redusă la rulare reduce consumul de combustibil.
- Datorită peretelui lateral ranforsat si a carcasei robuste ranforsată cu centură de otel, anvelopa este protejată în mod optim împotriva deteriorării.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.