Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 15.5 / 80 - 24, 324
12 PR, 157 A6 / 154 A8, TL
Alliance

Product-No.: 15222268

Hints and features:

- Anvelope AS cu straturi încrucisate pentru utilizare pe tractoare sau ca anvelope pentru utilaje.
- Crampoane dispuse la un unghi de 45° pentru tractiune ridicată si auto-curătare bună chiar si în cele mai dificile conditii.
- Carcasa puternică din nailon asigură siguranta operațională si o transmisie bună a tractiunii.

Technical Information:

Product number	15222268
Tyre Size	15.5 / 80 - 24
R / D	Diagonală
TL / TT	TL
LI / SI	157 A6 / 154 A8
PR	12
Profil	324
Manufacturer	Alliance
Recom. Rim	12
Permissible rim	14
Width mm	394
Outer diameter mm	1240
Static radius mm	558
Rolling circumference mm	3786
Payload in kg at kph (1)	4125 / 30
Payload in kg at kph (2)	3750 / 40
Inflation pressure bar	3,00
Weight kg	65,12
Tyre content 75% litre	166.2
Stud width mm	52-34
Stud height mm	38,0
Number of studs	18x2
Certified	ECE 106
Nominal width [inch]	15.5
Aspect ratio	80
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.