Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu IF 650 / 65 R 34 CFO, Agriflex 372 161 D, TL, Steel Belted Alliance

Product-No.: 15225178

Technical Information:

Product number	15225178
Tyre Size	IF 650 / 65 R 34 CFO
R / D	Radial
TL / TT	TL
LI / SI	161 D
Profil	Agriflex 372
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	23
Width mm	650
Outer diameter mm	1720
Static radius mm	769
Rolling circumference mm	5033
Payload in kg at kph (1)	4625 / 65
Inflation pressure bar	1,60
Weight kg	213,46
Tyre content 75% litre	579
Stud height mm	58,0
Number of studs	20x2
Certified	ECE 106
Cyclic field use	CFO
Nominal width [mm]	650
Aspect ratio	65
Tyre technology	IF

Hints and features:

- Anvelopa Alliance 372 este o anvelopă cu tehnologie IF pentru tractoare din gama superioară de putere începând de la cca. 220 CP.
- Peretii ei laterali extrem de flexibili permit o capacitate de încărcare cu 20% mai mare la aceeasi presiune atmosferică sau aceeasi capacitate de încărcare la o presiune atmosferică cu 20% mai scăzută comparativ cu o anvelopă standard.
- Banda sa de contact mărită asigură o tractiune foarte bună si, astfel, un consum redus de combustibil.
- În acelasi timp, compactarea solului este redusă, iar solul este protejat în mod optim.
- Profilul ei R-1W oferă anvelopei o aderentă foarte bună si o durată lungă de viată.
- Anvelopa este adecvată pentru utilizarea ciclică în câmp (CFO) pe masini de recoltat.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.