Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 800 / 70 R 32 CHO, Agristar 375 175 A8 / 175 B, TL, Steel Belted Alliance

Product-No.: 15225283

Technical Information:

Product number	15225283
Tyre Size	800 / 70 R 32 CHO
R / D	Radial
TL / TT	TL
LI / SI	175 A8 / 175 B
Profil	Agristar 375
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	27
Permissible rim	25
Width mm	770
Outer diameter mm	1936
Static radius mm	877
Rolling circumference mm	5706
Payload in kg at kph (1)	6900 / 40
Payload in kg at kph (2)	6900 / 50
Inflation pressure bar	2,40
Weight kg	382,16
Tyre content 75% litre	926
Stud height mm	65,0
Number of studs	21x2
Certified	ECE 106
Cyclic field use	CHO
Nominal width [mm]	800
Aspect ratio	70
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelope super voluminoase pentru masini de recoltat, masini autopropulsate de împrăstiat nutrienti si alte utilaje agricole grele.
- Profil agresiv R-1W pentru tractiune maximă si alunecare redusă.
- Oferă capacităti portante enorme chiar si la presiuni scăzute ale aerului.
- Centurile de otel si compusul special de cauciuc Stubble Guard fac ca anvelopa să fie si mai robustă, de exemplu împotriva deteriorării cauzate de miristea de porumb.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.