Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 710 / 75 R 34, Agristar 375
178 A8 / 178 B, TL
Alliance

Product-No.: 15225290

Technical Information:

Product number	15225290
Tyre Size	710 / 75 R 34
R / D	Radial
TL / TT	TL
LI / SI	178 A8 / 178 B
Profil	Agristar 375
Manufacturer	Alliance
Recom. Rim	23
Permissible rim	21
Width mm	720
Outer diameter mm	1945
Static radius mm	880
Rolling circumference mm	5789
Payload in kg at kph (1)	7500 / 40
Payload in kg at kph (2)	7500 / 50
Inflation pressure bar	3,20
Weight kg	319,32
Tyre content 75% litre	832.5
Stud height mm	58,0
Number of studs	20x2
Certified	ECE 106
Nominal width [mm]	710
Aspect ratio	75
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelope super voluminoase pentru masini de recoltat, masini autopropulsate de împrăstiat nutrienti si alte utilaje agricole grele.
- Profil agresiv R-1W pentru tractiune maximă si alunecare redusă.
- Oferă capacităti portante enorme chiar si la presiuni scăzute ale aerului.
- Centurile de otel si compusul special de cauciuc Stubble Guard fac ca anvelopa să fie si mai robustă, de exemplu împotriva deteriorării cauzate de miristea de porumb.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.