Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



# Pneu 320 / 90 R 46, 350 151 A8 / 148 D, TL (12.4R46), Alliance

**Product-No.: 15226300**

**Technical Information:**

| | |
|---|---|
| Product number | 15226300 |
| Tyre Size | 320 / 90 R 46 |
| R / D | Radial |
| TL / TT | TL |
| LI / SI | 151 A8 / 148 D |
| Profil | 350 |
| Manufacturer | Alliance |
| Recom. Rim | 11 |
| Permissible rim | 9, 10 |
| Width mm | 315 |
| Outer diameter mm | 1727 |
| Static radius mm | 809 |
| Rolling circumference mm | 5279 |
| Payload in kg at kph (1) | 3450 / 40 |
| Payload in kg at kph (2) | 3150 / 65 |
| Inflation pressure bar | 3,60 |
| Weight kg | 83,04 |
| Tyre content 75% litre | 201.75 |
| Stud width mm | 28 |
| Stud height mm | 38,0 |
| Number of studs | 30x2 |
| Certified | ECE 106 |
| Nominal width [mm] | 320 |
| Aspect ratio | 90 |
| Direction bound | Yes |
| Tread symmetry | simetrice |

**Hints and features:**

- Anvelope pentru îngrijire pentru utilizare pe tractoare si pulverizatoare de câmp autopropulsate.
- Ideal pentru protectia plantelor si lucrările de îngrijire în culturile pe rânduri.
- Umerii rotunjiti protejează împotriva deteriorării plantelor si a solului.
- Disponibile în variante cu capacitate de încărcare foarte mare, chiar si pentru cele mai grele combinatii de utilaje (pulverizator de câmp + rezervor suplimentar).
- Omologare la 65 km/h (exceptii rezervate)

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.