Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 340 / 85 R 48, 350 154 A8 / 151 D, TL (13.6R48), Alliance

Product-No.: 15226395

Hints and features:

- Anvelope pentru îngrijire pentru utilizare pe tractoare si pulverizatoare de câmp autopropulsate.
- Ideal pentru protectia plantelor si lucrările de îngrijire în culturile pe rânduri.
- Umerii rotunjiti protejează împotriva deteriorării plantelor si a solului.
- Disponibile în variante cu capacitate de încărcare foarte mare, chiar si pentru cele mai grele combinatii de utilaje (pulverizator de câmp + rezervor suplimentar).
- Omologare la 65 km/h (exceptii rezervate)

Technical Information:

Product number	15226395
Tyre Size	340 / 85 R 48
R / D	Radial
TL / TT	TL
LI / SI	154 A8 / 151 D
Profil	350
Manufacturer	Alliance
Recom. Rim	12
Permissible rim	11
Width mm	345
Outer diameter mm	1805
Static radius mm	860
Rolling circumference mm	5621
Payload in kg at kph (1)	3750 / 40
Payload in kg at kph (2)	3450 / 65
Inflation pressure bar	4,20
Weight kg	102,15
Tyre content 75% litre	209.62
Stud height mm	39,5
Certified	ECE 106
Nominal width [mm]	340
Aspect ratio	85
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.