Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 620 / 75 R 26, Agristar 375 166 A8 / 166 B, TL, Steel Belted Alliance

Product-No.: 15226745

Hints and features:

- Anvelope super voluminoase pentru masini de recoltat, masini autopropulsate de împrăstiat nutrienti si alte utilaje agricole grele.
- Profil agresiv R-1W pentru tractiune maximă si alunecare redusă.
- Oferă capacităti portante enorme chiar si la presiuni scăzute ale aerului.
- Centurile de otel si compusul special de cauciuc Stubble Guard fac ca anvelopa să fie si mai robustă, de exemplu împotriva deteriorării cauzate de miristea de porumb.

Technical Information:

Product number	15226745
Tyre Size	620 / 75 R 26
R / D	Radial
TL / TT	TL
LI / SI	166 A8 / 166 B
Profil	Agristar 375
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	20
Permissible rim	18
Width mm	625
Outer diameter mm	1595
Static radius mm	727
Rolling circumference mm	4816
Payload in kg at kph (1)	5300 / 40
Payload in kg at kph (2)	5300 / 50
Inflation pressure bar	3,00
Weight kg	217,56
Tyre content 75% litre	517.5
Stud height mm	47,0
Certified	ECE 106
Nominal width [mm]	620
Aspect ratio	75
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.