Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 600 / 65 R 34, Agristar 365
160 A8 / 157 D, TL
Alliance

Product-No.: 15226811

Hints and features:

- Anvelope late radiale AS din seria 65 (seria 70 având o lătime de 710) pentru tractoare puternice de până la aprox. 250 CP.
- Prelucrare foarte delicată a solului datorită volumului mare de aer si a suprafetei mari de contact.
- Forma si dispunerea crampoanelor permit transmiterea optimă a tractiunii.
- Cu o omologare pentru 65 km/h, este potrivită pentru utilizarea frecventă pe sosea.

Technical Information:

Product number	15226811
Tyre Size	600 / 65 R 34
R / D	Radial
TL / TT	TL
LI / SI	160 A8 / 157 D
Profil	Agristar 365
Manufacturer	Alliance
Recom. Rim	18
Permissible rim	20
Width mm	591
Outer diameter mm	1644
Static radius mm	739
Rolling circumference mm	4904
Payload in kg at kph (1)	4500 / 40
Payload in kg at kph (2)	4125 / 65
Inflation pressure bar	2,40
Weight kg	166,87
Tyre content 75% litre	435
Stud height mm	55,0
Number of studs	20x2
Certified	ECE 106
Nominal width [mm]	600
Aspect ratio	65
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.