Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 420 / 80 R 46, 385
162 A8 / 159 D, TL, High Speed
Alliance

Product-No.: 15227412

Technical Information:

Product number	15227412
Tyre Size	420 / 80 R 46
R / D	Radial
TL / TT	TL
LI / SI	162 A8 / 159 D
Profil	385
Manufacturer	Alliance
Specification	High Speed
Recom. Rim	13
Permissible rim	12, 14
Width mm	420
Outer diameter mm	1861
Static radius mm	859
Rolling circumference mm	5611
Payload in kg at kph (1)	4750 / 40
Payload in kg at kph (2)	4375 / 65
Inflation pressure bar	3,20
Weight kg	153,02
Tyre content 75% litre	321
Certified	ECE 106
Nominal width [mm]	420
Aspect ratio	80
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelope radiale AS din seria 80/85 pentru tractoare din gama de putere de până la cca. 200 CP.
- Volum mare de aer pentru o capacitate portantă enormă si confort excelent la rulare.
- Profilul R-1W (adâncime a profilului cu 20% mai mare comparativ cu R-1) în combinatie cu un număr optimizat de crampoane asigură o tractiune bună si o auto-curătare.
- Talon si crampoane ranforsate pentru o durată lungă de viată.
- Compusul de cauciuc Stubble Guard oferă protectie împotriva deteriorării prin penetrare cauzate, de exemplu, de miristea de porumb.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.