Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 340 / 80 - 20, Tough Trac 325 144 A8, TL (12.5/80-20), Alliance

Product-No.: 15231500

Hints and features:

- Anvelopa Alliance 325 Tough Trac dispune de un profil al benzii de rulare directională specială cu crampoane masive, oferind o tractiune excelentă în toate conditiile.
- Constructia diagonală robustă asigură o stabilitate deosebită în modul de ridicare exigent.
- Peretele lateral si talonul suplimentar ranforsat oferă cea mai bună protectie pentru a minimiza deteriorarea în timpul aplicatiilor grele.
- Adecvat pentru buldoexcavatoare şi altele asemănătoare.

Technical Information:

Product number	15231500
Tyre Size	340 / 80 - 20
R / D	Diagonală
TL / TT	TL
LI / SI	144 A8
Profil	Tough Trac 325
Manufacturer	Alliance
Recom. Rim	11
Permissible rim	10, 12
Width mm	343
Outer diameter mm	1052
Static radius mm	474
Rolling circumference mm	3106
Payload in kg at kph (1)	2800 / 40
Inflation pressure bar	4,00
Weight kg	59,97
Stud height mm	27,0
Number of studs	20x2
Certified	ECE 106
Nominal width [mm]	340
Aspect ratio	80

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.