Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 440 / 80 - 24, Tough Trac 325 168 A8, TL (16.9-24), Alliance

Product-No.: 15231510

Technical Information:

Product number	15231510
Tyre Size	440 / 80 - 24
R / D	Diagonală
TL / TT	TL
LI / SI	168 A8
Profil	Tough Trac 325
Manufacturer	Alliance
Recom. Rim	DW14L
Permissible rim	W15L, DW15L
Width mm	441
Outer diameter mm	1314
Static radius mm	606
Rolling circumference mm	4020
Payload in kg at kph (1)	5600 / 40
Inflation pressure bar	5,00
Weight kg	101,19
Tyre content 75% litre	216
Stud height mm	34,8
Number of studs	18x2
Certified	ECE 106
Nominal width [mm]	440
Aspect ratio	80

Hints and features:

- Anvelopa Alliance 325 Tough Trac dispune de un profil al benzii de rulare directională specială cu crampoane masive, oferind o tractiune excelentă în toate conditiile.
- Constructia diagonală robustă asigură o stabilitate deosebită în modul de ridicare exigent.
- Peretele lateral si talonul suplimentar ranforsat oferă cea mai bună protectie pentru a minimiza deteriorarea în timpul aplicatiilor grele.
- Adecvat pentru buldoexcavatoare şi altele asemănătoare.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.