Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 480 / 80 R 34, Multiuse 550 164 A8 / 159 D, TL, Steel Belted, M+S (18.4R34), Bloc, Alliance

Product-No.: 15284111

Hints and features:

- Anvelope pentru utilaje ale gospodăriei comunale pentru utilizare versatilă, de exemplu, pentru tractoare în cadrul operatiunilor contractuale cu o proportie ridicată de utilizare a soselelor sau pentru recoltarea furajelor verzi si a porumbului.
- Performantă optimă pe timp de iarnă datorită profilului bloc special
- Rezistenta redusă la rulare permite economisirea combustibilului fată de anvelopele AS standard.
- Ranforsare cu centuri din oţel pentru o capacitate portantă ridicată si protectie împotriva deteriorărilor prin întepare.
- Cu marcaj M+S

Technical Information:

Product number	15284111
Tyre Size	480 / 80 R 34
R / D	Radial
TL / TT	TL
LI / SI	164 A8 / 159 D
Profil	Multiuse 550
Manufacturer	Alliance
Specification	M+S, Steel Belted
Recom. Rim	DW15L
Permissible rim	13, 14, 16
Width mm	479
Outer diameter mm	1632
Static radius mm	739
Rolling circumference mm	4912
Payload in kg at kph (1)	5000 / 40
Payload in kg at kph (2)	4375 / 65
Inflation pressure bar	3,20
Weight kg	152,59
Tyre content 75% litre	380.4
Stud height mm	27,0
Number of studs	48x2
Certified	ECE 106
M+S	M+S
Nominal width [mm]	480
Aspect ratio	80
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.