Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 335 / 80 R 18, 608 136 A8, TL, Steel Belted (12.5R18), Alliance

Product-No.: 15284870

Technical Information:

Product number	15284870
Tyre Size	335 / 80 R 18
R / D	Radial
TL / TT	TL
LI / SI	136 A8
Profil	608
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	11
Permissible rim	10
Width mm	339
Outer diameter mm	993
Static radius mm	449
Rolling circumference mm	2960
Payload in kg at kph (1)	2240 / 40
Inflation pressure bar	3,20
Weight kg	49,25
Stud height mm	24,2
Certified	ECE 106
Nominal width [mm]	335
Aspect ratio	80
Tread symmetry	simetrice

Hints and features:

- Anvelopă radială MPT pentru utilaje compacte / de constructii, cum ar fi excavatoare, încărcătoare frontale pe roti, încărcătoare telescopice si încărcătoare antiderapante cu direcţie.
- Bandă de contact solidă pentru stabilitate, în combinatie cu crampoane centrale late pentru suprafete dure.
- Crampoane înalte în zona umerilor pentru tractiune pe suprafete moi.
- Rezistenta optimizată la rulare permite economii de combustibil.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.