Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 335 / 80 R 20, 608 147 A2 / 136 B, TL, Steel Belted (12.5R20), Alliance

Product-No.: 15284907

Technical Information:

Product number	15284907
Tyre Size	335 / 80 R 20
R / D	Radial
TL / TT	TL
LI / SI	147 A2 / 136 B
Profil	608
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	11
Permissible rim	W10, W11, 11SDC, 12, 12SDC
Width mm	350
Outer diameter mm	1044
Static radius mm	465
Rolling circumference mm	3148
Payload in kg at kph (1)	3075 / 10
Payload in kg at kph (2)	2240 / 50
Inflation pressure bar	3,75
Weight kg	49,49
Stud height mm	18,5
Number of studs	24x2
Certified	nu este necesar
Nominal width [mm]	335
Aspect ratio	80
Tread symmetry	Asimetric

Hints and features:

- Anvelopă radială MPT pentru utilaje compacte / de constructii, cum ar fi excavatoare, încărcătoare frontale pe roti, încărcătoare telescopice si încărcătoare antiderapante cu direcţie.
- Bandă de contact solidă pentru stabilitate, în combinatie cu crampoane centrale late pentru suprafete dure.
- Crampoane înalte în zona umerilor pentru tractiune pe suprafete moi.
- Rezistenta optimizată la rulare permite economii de combustibil.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.