Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 460 / 70 R 24, Agro Industrial 580 159 A8 / 159 B, TL, Steel Belted, C.R. (17.5LR24), Alliance

Product-No.: 15285312

Hints and features:

Technical Information:

Product number	15285312
Tyre Size	460 / 70 R 24
R / D	Radial
TL / TT	TL
LI / SI	159 A8 / 159 B
Profil	Agro Industrial 580
Manufacturer	Alliance
Specification	Steel Belted/C.R.
Recom. Rim	DW15L
Permissible rim	DW14L
Width mm	462
Outer diameter mm	1250
Static radius mm	573
Rolling circumference mm	3797
Payload in kg at kph (1)	4375 / 40
Payload in kg at kph (2)	4375 / 50
Inflation pressure bar	4,00
Weight kg	107,8
Tyre content 75% litre	198.75
Stud height mm	38,0
Number of studs	17x2
Certified	ECE 106
Nominal width [mm]	460
Aspect ratio	70
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.