Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 500 / 70 R 24, Agro Industrial 580 164 A8 / 164 B, TL, Steel Belted (19.5LR24), Alliance

Product-No.: 15285321

Hints and features:

- Anvelope Agro-Industriale / MPT pentru încărcătoare telescopice, încărcătoare frontale pe roti si buldoexcavatoare.
- Carcasa radială puternică asigură capacităti de încărcare ridicate si stabilitate maximă în timpul utilizării.
- Compus de cauciuc optimizat si crampoane centrale unghiulare pentru suprafete dure.
- Rezistentă ridicată la uzură si, prin urmare, o durată lungă de viată.
- Optimă şi adecvată pentru instalatiile de biogaz.

Technical Information:

Product number	15285321
Tyre Size	500 / 70 R 24
R / D	Radial
TL / TT	TL
LI / SI	164 A8 / 164 B
Profil	Agro Industrial 580
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	16
Permissible rim	15
Width mm	505
Outer diameter mm	1308
Static radius mm	600
Rolling circumference mm	3983
Payload in kg at kph (1)	5000 / 40
Payload in kg at kph (2)	5000 / 50
Inflation pressure bar	4,00
Weight kg	117,13
Tyre content 75% litre	258.3
Stud height mm	38,0
Certified	ECE 106
Nominal width [mm]	500
Aspect ratio	70
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.