Bohnenkamp
Moving Professionals

WINDPOWER
Get Your Job Done



Pneu 315 / 70 R 22.5, PRO DR85 18 PR, 154 / 150 L (152 / 148 M), TL, 3PMSF HA, Windpower

Product-No.: 10466650

Technical Information:

Product number	10466650
Tyre Size	315 / 70 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	154 / 150 L (152 / 148 M)
PR	18
Profil	PRO DR85
Manufacturer	Windpower
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.75
Width mm	314
Outer diameter mm	1024
Static radius mm	477
Rolling circumference mm	3123
Payload in kg at kph (1)	3750 / 120
Payload in kg at kph (2)	3550 / 130
Inflation pressure bar	9,00
Weight kg	66,06
Rolling resistance	C
Wet grip	C
Rolling noise DB	73
Rolling noise level	A
Stud height mm	21,0
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	315
Aspect ratio	70
LI 4	148
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.