Bohnenkamp
Moving Professionals



Pneu 385 / 55 R 22.5, MTR96 20 PR, 160 K (158 L), TL, 3PMSF TR, Dynamo

Product-No.: 11666206

Technical Information:

Product number	11666206
Tyre Size	385 / 55 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	160 K (158 L)
PR	20
Profil	MTR96
Manufacturer	Dynamo
Specification	3PMSF
Recom. Rim	12.25
Permissible rim	11.75
Width mm	386
Outer diameter mm	996
Rolling circumference mm	3018
Payload in kg at kph (1)	4500 / 110
Payload in kg at kph (2)	4250 / 120
Inflation pressure bar	9,00
Weight kg	68,67
Rolling resistance	C
Wet grip	C
Rolling noise DB	72
Rolling noise level	B
Stud height mm	14,5
Certified	ECE 117, ECE 54
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	385
Aspect ratio	55
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.