Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu 500 / 70 R 24, Loadpro 164 A8 / 164 B, TL, Steel Belted (19.5LR24), CEAT

Product-No.: 15185314

Hints and features:

- Ceat Loadpro este o anvelopă radială MPT care poate fi utilizată pe manipulatoare telescopice.
- Peretele ei lateral ranforsat asigură o stabilitate excelentă.
- Carcasa cu centură din oţel (Steel Belted) şi talonul ranforsat al anvelopei, asigură o capacitate portantă ridicată şi o lungă durată de viaţă.

Technical Information:

Product number	15185314
Tyre Size	500 / 70 R 24
R / D	Radial
TL / TT	TL
LI / SI	164 A8 / 164 B
Profil	Loadpro
Manufacturer	CEAT
Specification	R4, Steel Belted
Recom. Rim	W16L
Permissible rim	W15L, W18L
Width mm	503
Outer diameter mm	1310
Static radius mm	617
Rolling circumference mm	3910
Payload in kg at kph (1)	5000 / 40
Payload in kg at kph (2)	5000 / 50
Inflation pressure bar	4,00
Weight kg	118,57
Tyre content 75% litre	242.00
Stud height mm	34,0
Number of studs	18x2
Certified	ECE 106
Nominal width [mm]	500
Aspect ratio	70
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.