Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu 500 / 60 R 22.5, Floatmax FT
155 D, TL, Steel Belted
CEAT

Product-No.: 15116210

Technical Information:

Product number	15116210
Tyre Size	500 / 60 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	155 D
Profil	Floatmax FT
Manufacturer	CEAT
Specification	Steel Belted
Recom. Rim	AG 16.00
Width mm	503
Outer diameter mm	1172
Static radius mm	530
Rolling circumference mm	3500
Payload in kg at kph (1)	3875 / 65
Payload in kg at kph (2)	5270 / 40
Inflation pressure bar	4,00
Weight kg	97,23
Tyre content 75% litre	217.00
Number of studs	22x2
Certified	ECE 106
Nominal width [mm]	500
Aspect ratio	60
Direction bound	Yes

Hints and features:

- Anvelopa Ceat Floatmax FT este o anvelopă radială pentru remorci agricole.
- Profilul directional al benzii de rulare, cu crampoane robuste, asigură o tractiune foarte bună, aderentă si auto-curătare.
- Blocurile robuste din centrul benzii de rulare si lătimea mare a benzii de rulare permit un comportament bun la rulare în timpul deplasării pe drumuri si o compactare mai redusă a solului în timpul lucrărilor pe câmp.
- Umărul rotunjit al anvelopei previne deteriorarea solului si a plantelor.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.