Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu 500 / 60 R 22.5, Floatmax RT
155 D, TL, Steel Belted
CEAT

Product-No.: 10000967

Technical Information:

Product number	10000967
Tyre Size	500 / 60 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	155 D
Profil	Floatmax RT
Manufacturer	CEAT
Specification	I2, Steel Belted
Recom. Rim	AG16.00
Width mm	503
Outer diameter mm	1172
Static radius mm	530
Rolling circumference mm	3500
Payload in kg at kph (1)	3875 / 65
Payload in kg at kph (2)	5270 / 40
Inflation pressure bar	4,00
Weight kg	100,4
Tyre content 75% litre	217.00
Stud height mm	17,5
Number of studs	12x2
Certified	ECE 106
Nominal width [mm]	500
Aspect ratio	60
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Floatmax RT este o anvelopă radială pentru remorci agricole, mini-cisterne, masini de împrăstiat îngrăsăminte (masini de fertilizat) si vehicule similare.
- Profilul special permite o auto-curătare foarte bună.
- Compusul de cauciuc rezistent si carcasa din nailon puternic asigură o bună protectie împotriva uzurii premature si o capacitate mare de încărcare la viteze mari.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.