Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 400 / 80 R 24, 585 162 A8 / 162 B, TL, Steel Belted (14.9R24), Alliance

Product-No.: 10000976

Technical Information:

Product number	10000976
Tyre Size	400 / 80 R 24
R / D	Radial
TL / TT	TL
LI / SI	162 A8 / 162 B
Profil	585
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	DW13
Permissible rim	W12, W13, W14L, DW12, DW14L
Width mm	404
Outer diameter mm	1250
Static radius mm	567
Rolling circumference mm	3752
Payload in kg at kph (1)	4750 / 40
Payload in kg at kph (2)	4750 / 50
Inflation pressure bar	5,00
Weight kg	106,1
Tyre content 75% litre	180.15
Stud height mm	33,0
Number of studs	26x2
Certified	ECE 106
Nominal width [mm]	400
Aspect ratio	80
Tread symmetry	simetrice

Hints and features:

- Anvelopa Alliance 585 este o anvelopă pentru manipulatoare telescopice, excavatoare si încărcătoare antiderapante cu directie.
- Este potrivită pentru utilizare în agricultură si pe santierele de constructii.
- Profilul benzii de rulare voluminos, non-directional asigură o tractiune bună si performante bune chiar si pe suprafete dure.
- Adâncimea mare a profilului suprafetei de rulare garantează o durată lungă de viată a anvelopei si o bună protectie împotriva deteriorării anvelopei.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.