Bohnenkamp
Moving Professionals

CEAT SPECIALTY



# Pneu VF 480 / 80 R 50, Spraymax 179 D, TL, Steel Belted CEAT

**Product-No.: 10001142**

**Hints and features:**

- Anvelopa Ceat Spraymax este o anvelopă VF pentru vehicule de pulverizare autopropulsate.
- Datorită tehnologiei VF, anvelopa oferă o capacitate de încărcare cu până la 40% mai mare decât o anvelopă standard sau aceeasi capacitate de încărcare la o presiune de aer cu până la 40% mai mică.
- Crampoanele aranjate sub formă de trepte asigură o bună aderentă si tractiune.
- Umerii rotunjiti ai anvelopei protejează solul si plantele.
- Adâncimea mare a benzii de rulare garantează o durată de viată deosebit de îndelungată.

**Technical Information:**

| | |
|---|---|
| Product number | 10001142 |
| Tyre Size | VF 480 / 80 R 50 |
| R / D | Radial |
| TL / TT | TL |
| LI / SI | 179 D |
| Profil | Spraymax |
| Manufacturer | CEAT |
| Specification | R1, Steel Belted |
| Recom. Rim | DW16 |
| Permissible rim | DW15 |
| Width mm | 479 |
| Outer diameter mm | 2060 |
| Static radius mm | 951 |
| Rolling circumference mm | 6148 |
| Payload in kg at kph (1) | 7750 / 65 |
| Payload in kg at kph (2) | 7750 / 40 |
| Inflation pressure bar | 3,60 |
| Weight kg | 217,18 |
| Tyre content 75% litre | 442.00 |
| Stud height mm | 41,0 |
| Certified | ECE 106 |
| Nominal width [mm] | 480 |
| Aspect ratio | 80 |
| Tyre technology | VF |
| Direction bound | Yes |
| Tread symmetry | simetrice |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.