Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu 620 / 75 R 30 CHO, Yieldmax 169 A8 / 169 B, TL, Steel Belted CEAT

Product-No.: 10000326

Technical Information:

Product number	10000326
Tyre Size	620 / 75 R 30 CHO
R / D	Radial
TL / TT	TL
LI / SI	169 A8 / 169 B
Profil	Yieldmax
Manufacturer	CEAT
Specification	R1, Steel Belted
Recom. Rim	DW20B
Permissible rim	DW20L
Width mm	625
Outer diameter mm	1692
Static radius mm	763
Rolling circumference mm	5103
Payload in kg at kph (1)	5800 / 40
Payload in kg at kph (2)	5800 / 50
Inflation pressure bar	3,20
Weight kg	237,22
Tyre content 75% litre	523.00
Stud height mm	53,0
Certified	ECE 106
Cyclic field use	CHO
Nominal width [mm]	620
Aspect ratio	75
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Yieldmax este o anvelopă radială pentru combine, maşini de tocat lemne sau furaje si alte masini de recoltat, de exemplu pentru trestie de zahăr.
- Profilul acesteia cu crampoane dublu-angulare si umărul puternic si unghiular al anvelopei asigură o tractiune foarte bună si stabilitate laterală pe teren.
- Crampoanele se suprapun în centrul benzii de rulare, ceea ce permite o bună manevrabilitate în timpul transportului pe stradă.
- Carcasa puternică garantează capacităti mari de încărcare si o durată lungă de viată anvelopei.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.