Bohnenkamp
Moving Professionals

CEAT SPECIALTY



# Pneu 750 / 65 R 26 CHO, Yieldmax 173 A8 / 173 B, TL, Steel Belted CEAT

**Product-No.: 10000776**

**Technical Information:**

| | |
|---|---|
| Product number | 10000776 |
| Tyre Size | 750 / 65 R 26 CHO |
| R / D | Radial |
| TL / TT | TL |
| LI / SI | 173 A8 / 173 B |
| Profil | Yieldmax |
| Manufacturer | CEAT |
| Specification | R1, Steel Belted |
| Recom. Rim | DW25B |
| Permissible rim | DW24B, DW23B |
| Width mm | 754 |
| Outer diameter mm | 1625 |
| Static radius mm | 738 |
| Rolling circumference mm | 4824 |
| Payload in kg at kph (1) | 6500 / 40 |
| Payload in kg at kph (2) | 6500 / 50 |
| Inflation pressure bar | 3,60 |
| Weight kg | 239,29 |
| Tyre content 75% litre | 622.00 |
| Stud height mm | 54,0 |
| Number of studs | 18x2 |
| Certified | ECE 106 |
| Cyclic field use | CHO |
| Nominal width [mm] | 750 |
| Aspect ratio | 65 |
| Direction bound | Yes |
| Tread symmetry | simetrice |

**Hints and features:**

- Anvelopa Ceat Yieldmax este o anvelopă radială pentru combine, maşini de tocat lemne sau furaje si alte masini de recoltat, de exemplu pentru trestie de zahăr.
- Profilul acesteia cu crampoane dublu-angulare si umărul puternic si unghiular al anvelopei asigură o tractiune foarte bună si stabilitate laterală pe teren.
- Crampoanele se suprapun în centrul benzii de rulare, ceea ce permite o bună manevrabilitate în timpul transportului pe stradă.
- Carcasa puternică garantează capacităti mari de încărcare si o durată lungă de viată anvelopei.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.