Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu VF 710 / 60 R 34, Agriflex 372 + 173 D, TL, Steel Belted
Alliance

Product-No.: 15225181

Technical Information:

Product number	15225181
Tyre Size	VF 710 / 60 R 34
R / D	Radial
TL / TT	TL
LI / SI	173 D
Profil	Agriflex 372 +
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	DW25B
Permissible rim	DW24B, DW27B
Width mm	710
Outer diameter mm	1715
Static radius mm	754
Rolling circumference mm	5105
Payload in kg at kph (1)	6500 / 65
Inflation pressure bar	2,00
Weight kg	241,6
Tyre content 75% litre	639.67
Stud height mm	53,6
Number of studs	19x2
Certified	ECE 106
Nominal width [mm]	710
Aspect ratio	60
Tyre technology	VF
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Alliance 372+ este o anvelopă cu tehnologie VF pentru tractoare din gama superioară de putere începând de la cca. 220 CP.
- Peretii ei laterali extrem de flexibili permit o capacitate de încărcare cu 40% mai mare la aceeasi presiune a aerului sau aceeasi capacitate de încărcare la o presiune atmosferică cu 40% mai mică comparativ cu o anvelopă standard.
- Banda sa de contact mărită asigură o tractiune foarte bună si, astfel, un consum redus de combustibil.
- În acelasi timp, compactarea solului este redusă, iar solul este protejat în mod optim.
- Profilul ei R-1W oferă anvelopei o aderentă foarte bună si o durată lungă de viată.
- Anvelopa este adecvată pentru utilizarea ciclică în câmp (CFO) pe masini de recoltat.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.