Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu VF 600 / 70 R 30, Torquemax 170 D, TL, Textil Belted CEAT

Product-No.: 15126846

Technical Information:

Product number	15126846
Tyre Size	VF 600 / 70 R 30
R / D	Radial
TL / TT	TL
LI / SI	170 D
Profil	Torquemax
Manufacturer	CEAT
Specification	R1-W, Textil Belted
Recom. Rim	DW21L
Permissible rim	DW20L
Width mm	603
Outer diameter mm	1602
Static radius mm	692
Rolling circumference mm	4731
Payload in kg at kph (1)	6000 / 65
Payload in kg at kph (2)	6000 / 40
Inflation pressure bar	2,40
Weight kg	195,11
Tyre content 75% litre	424.00
Stud height mm	53,5
Number of studs	20x2
Certified	ECE 106
Nominal width [mm]	600
Aspect ratio	70
Tyre technology	VF
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Torquemax este o anvelopă pentru tractoare de înaltă performantă.
- Designul său asigură o compactare mai redusă a solului, o tractiune ridicată si o bună manevrabilitate atât pe câmp, cât si la transportul pe sosea.
- Crampoanele anvelopei sunt usor înclinate în centrul benzii de rulare pentru a asigura caracteristici bune de rulare pe sosea.
- Unghiul mai plat al crampoanelor de pe umărul anvelopei asigură o tractiune excelentă în timpul lucrărilor pe câmp.
- Umerii rotunjiti ai anvelopei protejează solul si plantele.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.