Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 440 / 80 R 28, Agro Industrial 580 156 A8 / 156 B, TL, Steel Belted (16.9R28), Alliance

Product-No.: 10001686

Technical Information:

Product number	10001686
Tyre Size	440 / 80 R 28
R / D	Radial
TL / TT	TL
LI / SI	156 A8 / 156 B
Profil	Agro Industrial 580
Manufacturer	Alliance
Specification	R4, Steel Belted
Recom. Rim	DW14L
Permissible rim	15
Width mm	441
Outer diameter mm	1415
Static radius mm	644
Rolling circumference mm	4247
Payload in kg at kph (1)	4000 / 40
Payload in kg at kph (2)	4000 / 50
Inflation pressure bar	3,20
Weight kg	128,1
Tyre content 75% litre	257.47
Stud height mm	40,0
Number of studs	22x2
Certified	ECE 106
Nominal width [mm]	440
Aspect ratio	80
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelope Agro-Industriale / MPT pentru încărcătoare telescopice, încărcătoare frontale pe roti si buldoexcavatoare.
- Carcasa radială puternică asigură capacităti de încărcare ridicate si stabilitate maximă în timpul utilizării.
- Compus de cauciuc optimizat si crampoane centrale unghiulare pentru suprafete dure.
- Rezistentă ridicată la uzură si, prin urmare, o durată lungă de viată.
- Optimă şi adecvată pentru instalatiile de biogaz.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.