Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu VF 650 / 85 R 38, Agriflex 372 + 182 D, TL, Steel Belted
Alliance

Product-No.: 10002409

Technical Information:

Product number	10002409
Tyre Size	VF 650 / 85 R 38
R / D	Radial
TL / TT	TL
LI / SI	182 D
Profil	Agriflex 372 +
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	DW23B
Permissible rim	DW21B, DW20B
Width mm	663
Outer diameter mm	2071
Static radius mm	901
Rolling circumference mm	6049
Payload in kg at kph (1)	8500 / 65
Inflation pressure bar	2,00
Weight kg	327,3
Tyre content 75% litre	843.07
Stud height mm	63,0
Number of studs	22x2
Certified	ECE 106
Nominal width [mm]	650
Aspect ratio	85
Tyre technology	VF
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Alliance 372+ este o anvelopă cu tehnologie VF pentru tractoare din gama superioară de putere începând de la cca. 220 CP.
- Peretii ei laterali extrem de flexibili permit o capacitate de încărcare cu 40% mai mare la aceeasi presiune a aerului sau aceeasi capacitate de încărcare la o presiune atmosferică cu 40% mai mică comparativ cu o anvelopă standard.
- Banda sa de contact mărită asigură o tractiune foarte bună si, astfel, un consum redus de combustibil.
- În acelasi timp, compactarea solului este redusă, iar solul este protejat în mod optim.
- Profilul ei R-1W oferă anvelopei o aderentă foarte bună si o durată lungă de viată.
- Anvelopa este adecvată pentru utilizarea ciclică în câmp (CFO) pe masini de recoltat.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.