Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu VF 560 / 60 R 22.5, Floatmax VF X3 166 D, TL, Steel Belted
CEAT

Product-No.: 10002671

Technical Information:

Product number	10002671
Tyre Size	VF 560 / 60 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	166 D
Profil	Floatmax VF X3
Manufacturer	CEAT
Specification	Steel Belted
Recom. Rim	AG16.00
Width mm	556
Outer diameter mm	1250
Static radius mm	537
Rolling circumference mm	3730
Payload in kg at kph (1)	5300 / 65
Payload in kg at kph (2)	6837 / 40
Inflation pressure bar	3,20
Weight kg	123,46
Tyre content 75% litre	280.00
Stud height mm	22,5
Number of studs	11x2
Certified	ECE 106
Nominal width [mm]	560
Aspect ratio	60
Tyre technology	VF
Direction bound	Yes

Hints and features:

- Anvelopa Ceat Floatmax VF X3 este o anvelopă "flotation" VF de ultimă generatie.
- Este deosebit de potrivită pentru utilizarea pe remorci agricole, cărucioare încărcătoare, masini de împrăstiat îngrăsăminte (masini de fertilizat) si vehicule similare.
- Profilul directional al benzii de rulare, cu crampoane robuste, asigură o tractiune foarte bună, aderentă si auto-curătare.
- Carcasa ei puternică din otel si compusul robust de cauciuc garantează o bună rezistentă la uzură.
- Tehnologia VF permite aceeasi capacitate de încărcare cu o presiune de aer cu 40% mai mică în comparatie cu anvelopele standard de aceeasi dimensiune.
- Acest lucru înseamnă un consum mai mic de combustibil, o compactare mai redusă a solului si productii mai mari.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.