Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu VF 420 / 95 R 50, Spraymax
177 D, TL, Steel Belted
CEAT

Product-No.: 10002894

Technical Information:

Product number	10002894
Tyre Size	VF 420 / 95 R 50
R / D	Radial
TL / TT	TL
LI / SI	177 D
Profil	Spraymax
Manufacturer	CEAT
Specification	R1-W, Steel Belted
Recom. Rim	DW14
Permissible rim	W13
Width mm	419
Outer diameter mm	2068
Static radius mm	943
Rolling circumference mm	6204
Payload in kg at kph (1)	7300 / 65
Payload in kg at kph (2)	7300 / 40
Inflation pressure bar	3,60
Weight kg	203,92
Tyre content 75% litre	400.00
Stud height mm	52,0
Certified	ECE 106
Nominal width [mm]	420
Aspect ratio	95
Tyre technology	VF
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Spraymax este o anvelopă VF pentru vehicule de pulverizare autopropulsate.
- Datorită tehnologiei VF, anvelopa oferă o capacitate de încărcare cu până la 40% mai mare decât o anvelopă standard sau aceeasi capacitate de încărcare la o presiune de aer cu până la 40% mai mică.
- Crampoanele aranjate sub formă de trepte asigură o bună aderentă si tractiune.
- Umerii rotunjiti ai anvelopei protejează solul si plantele.
- Adâncimea mare a benzii de rulare garantează o durată de viată deosebit de îndelungată.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.