Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu VF 380 / 105 R 54, Spraymax
168 D, TL, Steel Belted
CEAT

Product-No.: 10002958

Hints and features:

- Anvelopa Ceat Spraymax este o anvelopă VF pentru vehicule de pulverizare autopropulsate.
- Datorită tehnologiei VF, anvelopa oferă o capacitate de încărcare cu până la 40% mai mare decât o anvelopă standard sau aceeasi capacitate de încărcare la o presiune de aer cu până la 40% mai mică.
- Crampoanele aranjate sub formă de trepte asigură o bună aderentă si tractiune.
- Umerii rotunjiti ai anvelopei protejează solul si plantele.
- Adâncimea mare a benzii de rulare garantează o durată de viată deosebit de îndelungată.

Technical Information:

Product number	10002958
Tyre Size	VF 380 / 105 R 54
R / D	Radial
TL / TT	TL
LI / SI	168 D
Profil	Spraymax
Manufacturer	CEAT
Specification	R1, Steel Belted
Recom. Rim	W13
Permissible rim	W12
Width mm	383
Outer diameter mm	2145
Static radius mm	984
Rolling circumference mm	6435
Payload in kg at kph (1)	5600 / 65
Payload in kg at kph (2)	5600 / 40
Inflation pressure bar	2,40
Weight kg	188,49
Tyre content 75% litre	383.00
Stud height mm	50,0
Certified	ECE 106
Nominal width [mm]	380
Aspect ratio	105
Tyre technology	VF
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.