Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu 560 / 60 R 22.5, Floatmax FT
164 D, TL, Steel Belted
CEAT

Product-No.: 10000426

Technical Information:

Product number	10000426
Tyre Size	560 / 60 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	164 D
Profil	Floatmax FT
Manufacturer	CEAT
Specification	Steel Belted
Recom. Rim	AG16.00
Width mm	543
Outer diameter mm	1244
Static radius mm	561
Rolling circumference mm	3810
Payload in kg at kph (1)	5000 / 65
Payload in kg at kph (2)	6800 / 40
Inflation pressure bar	5,00
Weight kg	116,83
Tyre content 75% litre	259.00
Stud height mm	26,0
Number of studs	22x2
Certified	ECE 106
Nominal width [mm]	560
Aspect ratio	60
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Floatmax FT este o anvelopă radială pentru remorci agricole.
- Profilul directional al benzii de rulare, cu crampoane robuste, asigură o tractiune foarte bună, aderentă si auto-curătare.
- Blocurile robuste din centrul benzii de rulare si lătimea mare a benzii de rulare permit un comportament bun la rulare în timpul deplasării pe drumuri si o compactare mai redusă a solului în timpul lucrărilor pe câmp.
- Umărul rotunjit al anvelopei previne deteriorarea solului si a plantelor.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.